



GENERAL NOTES:

1) MATERIAL: 6061-T6 PER QQ-A-200/8 OR ASTM B221
 MINIMUM TENSILE YIELD STRENGTH = 35 KSI
 MINIMUM ULTIMATE TENSILE STRENGTH = 38 KSI
 MINIMUM ELONGATION = 8%

A SAMPLE FROM EACH BATCH WILL BE PULL TESTED TO
 ASTM STANDARD B221 BY AN APPROVED TESTING FACILITY
 TO ENSURE THAT THE BATCH MEETS THE ABOVE
 MINIMUM MECHANICAL PROPERTIES

2) BREAK ALL SHARP CORNERS 0.010 MAX

3) ALL DIMENSIONS ARE IN INCHES

4) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED

5) PART NUMBER IS D3882-1-XXX WHERE XXX IS
 CUT LENGTH IN INCHES (EX. D3882-1-180 IS 180" LONG)

6) D3882-1 EXTRUSION MANUFACTURED FROM: DIE # DAA-6

D3882-1 EXTRUSION

RELEASED
 09/07/15

A	NEW ISSUE	RF	09.01.23
REV.	DESCRIPTION	BY	DATE
DESIGN	RF	DART AEROSPACE USA, INC. PORT HADLOCK, WA	
DRAWN	RF		
CHECKED		DRAWING NO.	REV. A
MFG. APPR.		D3882	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		EXTRUSION	NTS
DATE	09.01.23	COPYRIGHT © 2009 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	